

EXPOSED FASTENING SYSTEM

AVP




The AVP panel is used for wall application and features pencil ribs, providing improved aesthetics to the building design.

FEATURES AND BENEFITS

- ◆ The AVP panel allows for more insulation to be added behind the panel, providing greater insulating values that meet the energy codes and R-Value requirements.
- ◆ UL 263 internal fire rating is available.

PRODUCT SPECIFICATIONS

- ◆ **Applications:** Wall
- ◆ **Coverage Widths:** 36"
- ◆ **Rib Spacing:** 12" on center
- ◆ **Rib Height:** 1- $\frac{1}{8}$ "
- ◆ **Panel Attachment:** Exposed Fastening System
- ◆ **Gauges:** 26 (Standard); 22, 24, 29 (Optional)
- ◆ **Finishes:** Smooth (Standard); Embossed (Optional)
- ◆ **Coatings:** Galvalume Plus®, Signature® 200, Signature® 300



EXPOSED FASTENING SYSTEM

AVP

CATEGORY	CHARACTERISTIC	TEST METHOD	PURPOSE	RESULT
STRUCTURAL	Negative Wind Loads	AISI S100	North American Specification for the Design of Cold-Formed Steel Structural Members	See Section Properties and Allowable Load Table Section
	Positive Wind Load	AISI S100	North American Specification for the Design of Cold-Formed Steel Structural Members	See Section Properties and Allowable Load Table Section

Descriptions and specifications contained herein were in effect at the time this publication was approved for printing. In a continuing effort to refine and improve products, Ceco Building Systems reserves the right to discontinue products at any time or change specifications and/or designs without incurring obligation. To ensure you have the latest information available, please inquire or visit our website at cecobuildings.com.

